



### KIWI eksklusiv

**Use:** For gardening and in households, in agriculture for transporting water and air.  
**Material:** Plasticized PVC.  
**Design:** Inner tubing black, casing transparent green. Winding fabric casing.  
**Working temperature:** Water + 1°C to + 50°C, air - 5°C to + 50°C.  
**Advantages:** Higher resistance to algae formation. Resistant to deformation.

dimensions inner/outer		order number	length	operation pressure at 20° C		destruction pressure at 20° C
mm	"	code	m	water	air	bar
8/12,5	5/16	020101DC	50	15	11	45
10/14,5	3/8	020102DC	50	10	7,5	30
12,5/17	1/2	020103DC	15, 25, 50	12	8,5	35
16/22	5/8	020104DC	25, 50	10	7,5	30
19/24,5	3/4	020105DC	15, 25, 50	7	6	25
25,5/33	1	020106DC	15, 25, 50	6	5	20



### ROSA eksklusiv

**Use:** For gardening and in households, in agriculture for transporting water and air.  
**Material:** Plasticized PVC.  
**Design:** Inner tubing and casing transparent. Winding fabric casing.  
**Working temperature:** Water + 1°C to + 50°C, air - 5°C to + 50°C.  
**Advantages:** Resistant to deformation.

dimensions inner/outer		order number	length	operation pressure at 20° C		destruction pressure at 20° C
mm	"	code	m	water	air	bar
8/12,5	5/16	020101AA	50	15	11	45
10/14,5	3/8	020102AA	50	10	7,5	30
12,5/17	1/2	020103AA	25, 50	12	8,5	35
16/22	5/8	020104AA	25, 50	10	7,5	30
19/24,5	3/4	020105AA	25, 50	7	6	25
25,5/33	1	020106AA	25, 50	6	5	20



### MAT eksklusiv

**Use:** For gardening and in households, in agriculture for transporting water and air.  
**Material:** Plasticized PVC.  
**Design:** Inner tubing transparent, casing transparent green. Winding fabric casing.  
**Working temperature:** Water + 1°C to + 50°C, air - 5°C to + 50°C.  
**Advantages:** Resistant to deformation.

dimensions inner/outer		order number	length	operation pressure at 20° C		destruction pressure at 20° C
mm	"	code	m	water	air	bar
8/12,5	5/16	020101AF	50	15	11	45
10/14,5	3/8	020102AF	50	10	7,5	30
12,5/17	1/2	020103AF	15, 25, 50	12	8,5	35
16/22	5/8	020104AF	25, 50	10	7,5	30
19/24,5	3/4	020105AF	15, 25, 50	7	6	25
25,5/33	1	020106AF	15, 25, 50	6	5	20



